



PC Board Layout
Component Side Shown

NOTES:

MATERIAL:

1. HOUSING MATERIAL : GLASS FILLED POLYESTER UL94V-0.
2. CONTACT MATERIAL : PHOSPHOR BRONZE $\phi=0.46\text{mm}$.
3. PLATING : SELECTING GOLD PLATING $3\mu\sim 50\mu$ NICKEL

ELECTRICAL:

1. VOLTAGE RATING : 125 VAC RMS.
2. CURRENT RATING : 1.5 AMP.
3. CONTACT RESISTANCE : 30 MILLIOHMS MAX.
4. INSULATION RESISTANCE : 500 MEGOHMS MIN @ 500V DC .
5. DIELECTRIC WITHSTANDING RESISTANCE : 1000V AC RMS 50Hz. 1MIN.

MECHANICAL:

1. DURRABILITY: : 750 CYCLES MIN.
2. PCB RETENTION PRE-SOLDER : 1 LB MIN.

ENVIRONMENTAL:

1. STORAGE : -40° C TO 85° C.
2. OPERATION : 0° C TO 70° C.

PART NUMBER:

MM CINCH		DFTO: SHB	DATE: 2007.05.05	Coorle 库乐科技
TOLERANCES EXCEPT AS NOTED		CHKD: LANBD	DATE: 2007.05.05	
MM		MFO:	DATE:	
.0 ± 0.15 .00 ± 0.075 .000 ± 0.05		APPL:	DATE:	
ANGLES ± 0.5		MATERIAL :		TITLE
THIRD ANGLE PROJECTION		QTY :		52E TOP ENRY JACK 1*4
SCALE :		FINISH :		DRAWING NO. TE52E1003
				/PART NO.
				DO NOT SCALE DRAWING
				SHEET X OF