



**SPECIFICATIONS:**  
 Contact current Rating:  
 1.8 Amperes for pin1&pin4.  
 0.25 Amperes other contacts  
 Dielectric Withstanding Voltage:AC 100V(RMS)  
 Insulation resistance:100Megohms Minimum.  
 Contact Resistance:  
 30mΩ Max for pin1&pin4  
 50mΩMax for other contacts  
**Mechanical Characteristics:**  
 Mating Force:35 Newtons.Maximum  
 Unmating Force:10 Newtons.Minimum.  
**MATERIAL:** 8N Min After Durability  
 Housing: PBT+30%GF 94V-0 COLOR:BLUE  
 Contact: copper alloy  
 Shell: SPCC  
**PLATING:**  
 Contact: Au Plated on contact area  
 Tin Plated on solder area  
 Nickel underplating over all  
 Shell: Nickel Plated/Gold flash  
 operating Temperature:-55'to+85'

Pin NUMBER	SIGNAL NAME	DONGGUAN CITY COORLE TECHNOLOGY CO.,LTD			
1	VBUS	UNLESS OTHERWISE SPECIFIED TOLERANCES X. +/- METRIC 0.30 .X +/- 0.25 .XX +/- 0.25 FRACTIONS +/- ANGLES +/- 2.00° DIMENSIONS (METRIC) (MM)	APPROVAL	日期	品名
2	D-		制图 WEIMINGJUN	2012.03.20	规格
3	D+		审核 xudongbin	2012.03.20	料号
4	GND		核准 xudongbin	2012.03.20	文件位置
5	StdA_SSRX-		ANGLE OF PROJECTION		字张
6	StdA_SSRX+				工程图号:
7	GND_DRAIN				版本:
8	StdA_SSTX-		A4		DWG-USB AM-003
9	StdA_SSTX+		1 : 1 状态码 A 页数 1 OF 1		A2
Shell	Shield				