



RECOMMEND P.C.B Layout (T=1.20mm)
PCB TOLERANCE;±0.05

版本 REV	编号 ECN NO.	位置 LOCATIONS	变更内容 DESCRIPTION	日期 DATE	变更人 DESIGN
B0			变更长度尺寸由13.30改为14.50		

NOTES:

1:MATERIAL:

<1>SHIELD:BRASS,T=0.2mm

<2>HOUSING:LCP,G/F FILLED,UL94V-0 RATED
OR OTHER HIGH PERFORMANCE RESINS.
COLOR IN BLACK.

<3>TERMINAL:PHOSPHOR BRONZE,T=0.35mm

2:CONTACT PLATED:GOLD

3:PCB TOLERANCES:DIMENSION ±0.05

4:RETENTION FORCE OF PLUG IN THE JACK IS 10 kgf(min).

5:SPECIFICATIO:

DIELECTRIC STRENGTH:AC 500V FOR ONE MINUTE

INSULATOR RESISTANCE:100M min.AT DC 100V

CONTACT RESISTANCE:45m max.

CURRENT RATING:500mA

OPERATING TEMPERATURE:-30°C ~+85°C

库乐科技

品名 TITLE:	RJ45. 沉板 H5.5	制图 (DR):	蒋伟	日期 (Date):	09.10.25
料号 (P/N):	L60055-14XXX	审核 (CHKD):		日期 (Date):	
模号 (M/N):		核准 (APPD):		日期 (Date):	
比例 (SCALE)	1:1	单位 (UNITE)	mm	张数 (SHEET):	XOFOX
				SIZE A4	级别 TYPE:

TOLERANCE UNLESS OTHERWISE SPECIFIED	
LINER	ANGLES
.0 ± 0.3	0.° ± 2.0°
.00 ± 0.2	.0° ± 1.0°
.000 ± 0.1	.00° ± 0.5°