



PCB.LaYoUT

特性:Specifications:

电器:Electrical:

接触阻抗:Contact Resistance

30 milliohms MAX

耐电压:Dielectric Withstanding Voltage:

500 V AC AT Sea Level

绝缘阻抗:Insulation Resistance:

1000 MEGA ohms MIN

机构:Mechanical:

结合为:Mating Force:

MAX:最大4kg/f

拔出力:Unmating Force:

MIN:最少0.7kg/f

材料:Material:

塑胶:Housing:High Temperature Thermoplastics

UL 94V-0 耐高温塑胶

端子:Contact:Copper Alloy 铜合金

铜壳:Shell: Copper Alloy铜合金

电镀:Finish:

端子:Contact: Plated Gold in Mating Area;

Tin/ On Solder Tails

接触点镀金.脚镀锡

铜壳:Shell:

Nickel Plating

镀镍

△ △ △ △				Unless otherwise specified tolerances are 未注尺寸公差		客户 Customer	编号 NO.		图号 Drawing NO.	设计 Designed by	审核 Checked by	批准 Approved by	共 1 张第 1 张 Sheet 0F	
				X	±0.3	品名 Item	USB BF 90°		装配图	刘俊			Third Angle Project	
				X.X	±0.2	版本 REV	材质 Material	厚度 MAT. THICK	数量 Amount	表面处理	交期	单位 Unit	比例 Scale	DWG F U H L W 0 1 / I / D W C / A 母
				X.XX	±0.1	A	SPCC	0.30			07.**	mm	FREE	
				X.XXX	±0.05									
			X.XXXX	±										
变更内容 Midify content		签名 Sign by	审核 Checked by	日期 Date	ANGLES ±0° SURFACE TEXTURE									